

## RA N Male Low PIM Connector Solder Attachment for TFT-5G-402



### TC-402-NM-RA-LP



## Times Microwave Systems Connector Specification

### Configuration

- N Male Connector
- 50 Ohms
- Right Angle Body Geometry
- Connector Interface Types: TFT-5G-402
- Low PIM Design

### Features

- Operating Frequency of 6 GHz Max.
- Good VSWR of 1.3:1
- PIM levels better than -160 dBc
- Silver Plated Brass Contact
- 5  $\mu$ m contact plating
- IP 67 Rated

### Applications

- General Purpose Test
- Wireless Communications
- Custom Cable Assemblies
- Low PIM Applications
- Distributed Antenna Systems (DAS)

### Description

RA type N Male Low PIM Connector Solder/Solder Attachment for TFT-5G-402 Cable, part number TC-402-NM-RA-LP, from Fairview Microwave is in-stock and ships same day. This type N male connector operates up to a maximum frequency of 6 GHz and offers good VSWR of 1.3:1. The type N male connector also has low passive intermodulation (PIM) of -160 dBc. Its right angle body geometry facilitates connections in tight spaces. Our TC-402-NM-RA-LP connector has an IP67 rating to protect against dust and temporary moisture protection under immersion conditions.

Fairview's RA type N male connector TC-402-NM-RA-LP datasheet specifications and outline drawing are shown in this PDF below. Our extensive offering of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. From providing an I/O for a board design to creating a custom cable assembly configuration, Fairview Microwave has a connector solution to meet your needs. Fairview Microwave also has the expertise to build your custom cable assemblies for you and ship them same-day.

### Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		6	GHz
VSWR			1.3:1	
Insertion Loss			0.1	dB
Passive Intermodulation			-160	dBc
Operating Voltage (DC)			1,000	Vdc
Inner Conductor DC Resistance			1	mOhms
Outer Conductor DC Resistance			1	mOhms
Insulation Resistance	5,000			MOhms
Impedance		50		Ohms

Electrical Specification Notes:  
Insertion Loss is  $0.1 \times \sqrt{f(\text{GHz})}$

## RA N Male Low PIM Connector Solder Attachment for TFT-5G-402



### TC-402-NM-RA-LP

#### Mechanical Specifications

<b>Size</b>	
Length	1.094 in [27.79 mm]
Width	0.37 in [9.40 mm]
Height	0.37 in [9.4 mm]
Weight	0.105 lbs [47.63 g]
Mating Torque	10 in-lbs [[1.13 Nm]]

#### Material Specifications

Description	Material	Plating
Contact	Brass	Silver 5 µm
Insulation	PTFE	
Body	Brass	Tri-Metal 3 µm
Coupling Nut	Brass	Tri-Metal 3 µm
Gasket	Silicone Rubber	

#### Environmental Specifications

<b>Temperature</b>	
Operating Range	-55 to +155 deg C
Ingress Protection (IP) Rating	IP 67 Rated
Shock	US MIL-STD 202, Meth. 213, Cond. I
Vibration	US MIL-STD 202, Meth. 204, Cond. B
Thermal Shock	US MIL-STD 202, Meth. 107, Cond. B

Environmental Specification Notes:  
Weather Standard: TEC 60068 55/155/21

#### Compliance Certifications (see [product page](#) for current document)

#### Plotted and Other Data

Notes:

## RA N Male Low PIM Connector Solder Attachment for TFT-5G-402



### TC-402-NM-RA-LP

RA N Male Low PIM Connector Solder Attachment for TFT-5G-402 from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Lewisville, Texas. Fairview Microwave is RF on-demand.

For additional information on this product, please click the following link: [RA N Male Low PIM Connector Solder Attachment for TFT-5G-402 TC-402-NM-RA-LP](#)

URL: <https://www.fairviewmicrowave.com/n-male-tft-402-connector-tc-402-nm-ra-lp-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume liability arising out of the use of any part or document.

TC-402-NM-RA-LP CAD Drawing
RA N Male Low PIM Connector Solder Attachment for TFT-5G-402

